

**API 5L GR.B/ASTM A53 GR.B
Hot Expanded ERW Steel Pipe**

OD 外径 (mm)	WT 壁厚 (mm)	EXW (USD/TON)
245, 273	5.0-9.28	597.92
	9.45-9.98	600.49
	10.0-11.78	603.05
299	5.0-9.28	597.92
	9.45-9.98	600.49
	10.0-11.78	603.05
325	5.5-9.28	603.05
	9.48-10.48	605.62
	10.58-11.78	608.18
351, 355, 377	5.5-11.98	613.31
	12.0-15	619.73
	15.5-16	626.14
402, 406, 426	5.5-11.98	617.16
	12.0-14.5	623.57
	15.5-16	629.99
OD 外径 (mm)	WT 壁厚 (mm)	EXW (USD/TON)
450, 457, 508, 530	6.5-11.98	629.99
	12.0-14.5	636.40
	15.0-17.8	642.81
	18.0-20.0	662.05
560, 610, 630	6.5-11.98	642.81
	12.0-14.5	649.22
	15.0-17.8	655.64
	18.0-20.0	674.87
660	7.5-11.98	687.70
	12.0-14.5	700.53
	15	713.35
720, 820	8.5	700.53
	12.0-14.5	706.94
	15.0-19.98	713.35
	18.0-20.0	726.18